

Large Medicine Stability Testing Chamber



LHH-500 series
LHH-800 series



LHH-1000 series
LHH-1500 series

Specifications

Model	LHH-500SD LHH-500SDP	LHH-800SD LHH-800SDP	LHH-1000SD LHH-1000SDP	LHH-1500SD LHH-1500SDP	LHH-500GSD LHH-500GSP	LHH-800GSD LHH-800GSP	LHH-1000GSD LHH-1000GSP LHH-1500GSP
Temperature control range	0~65°C				0~65°C without illumination 15~50°C with illumination		
Temperature Stability	±0.5°C						
Temperature uniformity	±2°C ~ ±3°C						
Humidity Rang	35~95%RH						
Humidity Stability	±3%RH						
Illumination	/				0~6000LX adjustable		
Illumination difference	/				≤±500LX		
Cooling system cooling mode	Two sets of imported compressor work rotationally						
Controller	Programmable (touch screen)						
Sensor	Temp: Pt100, Humidity: capacitance sensor						
Ambient Temperature	RT+5~30°C						
Electrical Requirement	AC220V 50Hz			AC380V 50HZ	AC220V 50Hz		AC220V 50Hz AC380V 50HZ
Power Consumption	3750W	3400W	3500W	6000W	3910W	3600W	3700W 6000W
Operating Power	1400W	2720W	2800W	4800W	1400W	2880W	2960W 4800W
Chamber Volume	500L	800L	1000L	1500L	500L	800L	1000L 1500L
Interior Dimension (WxDxH)mm	670×725×1020	800×590×1650	1050×590×1650	1550×590×1650	670×725×1020	800×590×1650	1050×590×1650 1550×590×1650
External Dimension (WxDxH)mm	850×1100×1930	1360×890×2000	1610×890×2000	2110×890×2000	850×1100×1930	1360×890×2000	1610×890×2000 2110×890×2000
Shelves	4(pcs)						
Safety Device	Compressor overheating and overpressure protection, Fan overheating protection Over temperature protection, Overload protection, Water protections						
Remark	1. Bulid in mini printer 2. Paperless recorder (Option). 3. GP/GSD/GSP series products have installed intensity of illumination detector. 4. GSD/GSP series products have 2 layers of light control (Option). 5. 1000L and 1500L are double doors						